

AquaCafé®

AquaCafé® **TOUCH** Bottled Water or Filtration Cooler



Features


- Single-serve coffee & tea in about 45 seconds, and hot & chilled water for residential and small offices
- Hotter water for barista quality coffee, tea, and for cooking instant noodles and soups
- Space saver — frees up counter space, no brewer or coffee pot on the counter or filtration system at the sink
- Time saver — Barista quality coffee brewed at home or office. No drive to expensive coffee house or waiting in line
- Brews 6, 8, 10, 12, and 14 ounce cup sizes
- Safety lock function for hot water
- Easy-to-use touch screen with illuminated dispensing area and brightness controls
- Adjustable drip tray that is removable for easy cleaning
- 1L / 0.28G stainless steel hot tank
- 3.78: / 1G cold tank
- Bottled water models load from the bottom so there is no lifting of heavy bottles — just slide into place
- Filtration models have room inside for single or dual icon eco3 filters or an RO system
- Sealed controls keep out dirt and liquid
- **Accu-Temp™** — Serves water at the proper temperature every time
- **Stay-Cool®** — Keeps residual water in the cold waterway chilled and ready to serve
- UL listed



aquabeve

AquaCafé®

AquaCafé® TOUCH Bottled Water or Filtration Cooler



Power

Voltage	115V
Frequency (Hz)	60
Total Power Consumption	1300W
Cold Power Consumption	100W
Hot Power Consumption	1200W

Brewer Hot Water System

Avg. Hot Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	194°F / 201.2°F
Hot Thermometer / Heat Limiter	221°F
Hot Thermostat / Thermistor Cycle	194°F - 201.2°F
Hot Tank Size (Liter : Gallon)	1L : 0.26G
Heating Element	Internal Heating Element

Hot Water System

Avg. Hot Water Temp at Nozzle @ 77°F Ambient (Cut-in / Cut-out Temp)	174.38°F / 194.9°F
Hot Water ARI Rating	121, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	221°F
Hot Thermostat / Thermistor Cycle	Cut-in: 72.4°F Cut-out: 190.4°F
Hot Water Flow Rate	0.49oz./sec
Heating Element	Internal Heating Element

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	45.7°F / 43.88°F
Cold Water ARI Rating	18, 5 oz. > 50°F +/- 10%
Cold Thermostat Set Point	Cut-in: 50°F Cut-out: 45°F
Cold Water Flow Rate	1.073 oz./sec
Cold Tank Size / Usable Volume(Liter : Gallon)	3.8 / 2.8 / 1.51 : 1 / 0.74

Weights and Measurements

Net Weight (H&C / C&C Lbs.)	37.48
Gross Weight (H&C / C&C Lbs.)	43.3
Max Distance from Drip Tray to Faucet (Adjustable) (Inch : mm)	8.75 : 222.25
Faucet / Dispense Height (Inch : mm)	37.5 : 952.5
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	17.04x14.09x43.5 / 17.52x14.76x45.67

Filter Compartment Dimensions

Width (Inch : mm)	12 : 304.79
Depth (Inch : mm)	11: 279.4
Inside Top to Bottom (Inch : mm)	21.75 : 323.85
Container Load (20')	224
Container Load (40')	462
Container Load (40' HC)	462
Container Load (45' HC)	518
Certifications	UL Listed
Models (BW : Filtration)	ACB 210r-T: ACB215 r-T

Warranty:

3 years: Sealed refrigeration system
 2 years: Parts (electrical to include cold controls, relay overloads and PCB's)

phone: (909) 629-7301
 Canada: (905) 302-7896
 email: info@aquabeve.com
 web: www.aquabeve.com

