

AquaHostess™ Bottled Water Cooler Filtration Cooler



Features

- 1.0L / .26G high energy hot tank
- 3.78L / 1G cold tank
- Available in filtration or bottled water models
- Bottled water models load from the bottom so there is no lifting of heavy bottles — bottle slides into place
- Filtration models have room inside for a single eco3 filter or dual filters, or an RO system
- Child safety lock function for hot water dispensing
- Easy-to-use touch screen with illuminated dispensing area and brightness control
- Stylish design fits in any home
- Available in black or red (special order)
- UL listed
- **Accu-Temp®** - Serves water at the proper temperature every time
- **Stay-Cool®** - Keeps the residual water in the cold waterway chilled and ready to serve at all times

Power

Voltage	115, 220, 110
Frequency (Hz)	50/60
Power Consumption	12A / 1300W / 115V
Cold Power Consumption	1.3A / 100W 115V
Hot Power Consumption	10.4A / 1200W / 115V
ES (kWh/24 hrs.)	0.80
% lower than ES Standard	8%

Hot Water System

Avg. Hot Water Temp at Nozzle @ 77°F Ambient (Cut-in / Cut-out Temp)	175°F : 190°F
Hot Water ARI Rating	121, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	221°F
Hot Thermostat / Thermistor Cycle	172°F - 190°F
Hot Water Flow Rate	0.49 oz./sec
Hot Water Flow Rate (oz per sec) with Accu-Temp Delay	0.47 oz./sec
Hot Tank Size (Liter : Gallon)	1.0L : 0.26G
Heat Band Wattage	1200W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	45°F / 42.8°F
Cold Water ARI Rating	16, 5 oz. < 50°F +/- 10%
Cold Thermostat Set Point	43°F - 48°F
Cold Water Flow Rate	1.07 oz/sec
Cold Water Flow Rate (oz per sec) with Accu-Temp Delay	1.06 oz./sec
Cold Tank Size / Usable Volume (Liter : Gallon)	3.78 / 2.8 : 1 / 0.74

Weights and Measurements

Net Weight / Gross Weight(Lbs.)	37.48 / 43.43
Max Distance from Drip Tray to Faucet (Adjustable) (Inch : mm)	8 : 203.2
Faucet / Dispense Height (Inch : mm)	37.5 : 952.5
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	17x14x43.5 / 17.5x14.8x45.7
Filter Compartment Dimensions WxDxH (inch : mm)	12 x 11 x 21.75 : 304.79 x 279.4 x 323.85
Container Load (20')	224
Container Load (40')	462
Container Load (40' HC)	462
Container Load (45' HC)	518
Certifications	UL Listed
Models (Bottled Water : Filtration)	ACB 210r, ACR 210r : ACB 215r, ACR 215r

Warranty:

3 years: Sealed refrigeration system
 2 years: Parts (electrical to include cold controls, relay overloads and PCB's)

phone: (909) 629-7301)

Canada: (905) 302-7896

email: info@aquabeve.com

web: www.aquabeve.com