

MTN

Horizons® 3Gg Filtration Cooler



Features

- 2.0L/0.53G insulated, stainless steel hot tank (HB215-3Gg only)
- 11.4L / 3G stainless steel cold tank
- Larger dispensing area for sport bottles & carafes
- Gravity dispensing
- Dual mechanical float
- Hot water child safety lock
- Room for internal mounting of an icon eco3 filter (single or dual) or RO system (75 GPD) (Sold Separately)
- Injection molded ABS
- Removable, dishwasher safe drip tray
- Stylish design fits in any office environment
- Custom colors and logos can be made available
- UL listed



Power

Voltage	115, 220, 110
Frequency (Hz)	50/60
Power Consumption (Tatung Compressor : Huayi Compressor)	4.89A / 563W / 115V : 4.05A / 520W / 115V
Cold Power Consumption (Tatung Compressor : Huayi Compressor)	1.44A / 118W 115V : 0.8A / 70W / 115V
Hot Power Consumption	3.87A / 449W / 115V
Energy Consumption (kWh/24 hrs.)	1.1 kWh / 24 hrs. (HB215-3Gg) 0.25 kWh / 24 hrs. (HB115-3Gg)

Hot Water System

Avg. Hot Water Temp at Nozzle @ 77°F Ambient (Cut-in / Cut-out Temp)	175.28°F / 188.17°F (HB215-3Gg Only)
Hot Water ARI Rating	46, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	203°F +/- 5.5°F
Hot Thermostat / Thermistor Cycle	168.8°F - 186.8°F
Hot Water Flow Rate	0.67 oz./sec
Hot Tank Size (L : G)	2.0L : 0.53G
Heat Band Wattage	450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	41°F / 45.5°F : 5°C / 7.5°C
Cold Water ARI Rating	61, 5 oz. < 50°F +/- 10%
Cold Water Flow Rate	0.95 oz./sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	11.35 / 9.46 / 3.36L : 3 / 2.5 / 0.89G

Weights and Measurements

Net Weight : Gross Weight (Lbs.)	54.67 / 58.67
Max Distance from Drip Tray to Faucet (Inch : mm)	20 : 254
Faucet / Dispense Height (Inch : mm)	35.5 : 901.7
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.5x15.3x44.6 / 13.2x16.2x45.7
Container Load (20') : (40')	186 : 383
Container Load (40' HC) : (45')	383 : 432

Filter Compartment Dimensions

Width (inches : mm)	10.75 : 273.05
Inside Top to Bottom (inch : mm)	17.5 : 444
Center Bracket to Bottom (inch : mm)	15 : 381
Depth without Bracket (inch : mm)	43 : 1092
Depth with Bracket (inch : mm)	43 : 1092
Models (H&C : C&C)	HB 215-3G-g : HB 115-3G-g

Warranty:

3 years: Sealed refrigeration system
 2 years: Parts (electrical to include cold controls, relay overloads and PCB's)

phone: (909) 629-7301)

Canada: (905) 302-7896

email: info@aquabeve.com

web: www.aquabeve.com