

# MTN

## Horizons® CT Filtration Cooler



### Features

- 1.4L / .37G stainless steel hot tank
- 3.55L / .94G stainless steel cold tank
- Larger 10" dispensing area to accommodate a variety of container sizes
- Lighted spout and dispensing area
- Safety lock for hot and cold water
- Features fast flow water dispensing
- Removable, dishwasher safe drip tray
- Available in black and white (special order)
- UL listed
- **Accu-Temp®** - Serve water at the proper temperature every time
- **Highly Energy Efficient** - Consumes less than one kWh/day in normal operating mode, and even less in Energy Saving mode
- **Stay-Cool®** - Keeps residual water in the cold waterway chilled and ready to serve



**Power**

Voltage	115, 220, 110
Frequency (Hz)	50/60
Power Consumption	4.83A / 547W / 115V
Cold Power Consumption	1.51A / 109.4W 115V
Hot Power Consumption	3.87A / 449W / 115V
ES (kWh/24 hrs.)	0.755
% lower than ES Standard	13%

**Hot Water System**

Avg. Hot Water Temp at Nozzle @ 77°F Ambient (Cut-in / Cut-out Temp)	172°F / 190°F
Hot Water ARI Rating	37, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	203°F
Hot Thermostat / Thermistor Cycle	140°F/ 198°F
Hot Water Flow Rate	1.24 - 1.46 oz./sec
Hot Tank Size (Liters / Gallons)	1.4L / 0.37G
Heat Band Wattage	450W

**Cold Water System**

Avg. Cold Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	48°F / 42°F
Cold Water ARI Rating	24, 5 oz. < 50°F +/- 10%
Cold Thermostat Set Point	45°F + 3°F/-8°F
Cold Water Flow Rate	1.24 - 1.46 oz./sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	3.55 / 2.64 / 1.32 : 0.94 / 0.7 / 0.35

**Weights and Measurements**

Net Weight (Lbs.)	35.3
Gross Weight (Lbs.)	38.4
Max Distance from Drip Tray to Faucet (Inch : mm)	10 : 254
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.8x17.1x17.5 / 13.4x17.7x18.5
Container Load (20')	340
Container Load (40')	700
Container Load (40' HC)	875
Container Load (45' HC)	979
Certifications	UL Listed
Models (H&C)	HCB 215

**Warranty:**

3 years: Sealed refrigeration system  
 2 years: Parts (electrical to include cold controls, relay overloads and PCB's)

**phone:** (909) 629-7301)

**Canada:** (905) 302-7896

**email:** info@aquabeve.com

**web:** www.aquabeve.com