



Commercial Counter Top Cooler



Features

- 3.94L / 1.04G stainless steel cold tank
- 60,000 cycles to meet the high demand of commercial environments
- Filtration beverage system with room inside for eco3 filter
- Touch sensitive screen for selecting beverage settings
- Antimicrobial faucet, drip tray, and dispense button
- Still or sparkling cold water and beverages
- Healthy cold beverages containing all natural flavors and real fruit juices
- Over 30 beverage flavors
- Beverages are all natural, preservative free, and 10 calories or less. Low or no sugar.
- 100% recyclable aluminum beverage capsules
- No trucking or hauling of bottled water and beverages
- UL listed



Features and Functions

Supports Standard 5 Gallon Bottles	Yes via pump kit from 5 gallon bottle (sold separately)
Temperature Adjustment	Yes-factory set and adjustable through touchscreen by technician
Beverage Size	12 ounces
Beverage Dispense Time	12 to 15 seconds
No Water Indicator	Yes
CO ₂ Level Sensor	Yes
Service Required Trigger	Yes
Menu System for Features	Yes
Sanitization	Ozone Sanitization Every Night

Cold Water System

Cycling Temperature Range in Cold Tank	3°C - 6°C
ARI Cold Capacity	27, 5 oz. < 50°F +/-10%
No Load	5 cups, 6 oz. < 10°C
Cold Water Flow Rate	0.85 oz./sec
Cold Tank Size / Usable Volume	145 x 152 x 273.8mm / 3.94L
Compressor	Huayi
Condensor	Aluminum Fin

Carbonation System

Soda Water Shot 12 oz	Yes
Low Level CO ₂ Sensor	Yes
Soda Water Flow Rate	0.071 oz./sec
Carbonation Level	CO ₂ > 2.8 at 3-5°C 3.5Bar
CO ₂ Bottle Size	1.68L, 2.2Lbs.
CO ₂ Bottle Quick Connect	Yes, Pin Valve
CO ₂ Bottle Connection	G1/2
CO ₂ Tank Volume	1200ml stored carbonated water, 500ml shot
Temperature	3°C to 5°C in the carbonation tank
Carbonated Water No Load	> 5 cups, 7 oz. > 2.8 volumes

Weights and Measurements

Net Weight /Gross Weight (Lbs.)	44 / 48
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	15.16x19.33x17.52 / 17.91x22.24x20.47
Nozzle to Drip Tray Height	8 inches
Drip Tray Volume	400ml
Container Load (20' : 40' : 40'HC : 45'HC)	208 : 420 : 525 : 464
Noise Level	< 50dB(A)
Certifications	UL Listed; FDA/NSF for all contact parts; CA prop 65, RoHS
Models	LB115

Warranty:

3 years: Sealed refrigeration system

2 years: Parts (electrical to include cold

controls, relay overloads and PCB's)

phone: (909) 629-7301

Canada: (905) 302-7896

email: info@aquabeve.com

web: www.aquabeve.com

