

MTN

Nexus™ LXp Bottled Water Cooler



Features

- 2.0L / .53G stainless steel hot tank
- 3.8L / 1G stainless steel cold tank
- Elevated dispensing height and larger dispensing area
- Hot and cold temperature indicator
- Child resistant hot water dispensing
- Unique, easy-dispense faucet
- Single dispense spigot for ease of filling
- Gravity fed, high-flow dispensing for fast fills
- Rugged HDPE cabinet for durability and easy cleaning
- Optional built-in cup dispenser (holds 3" diameter cups)
- Optional base plate for added stability
- Optional sealed hot controls
- Available in black with chrome accents
- UL listed
- **No Leak® EZ-Fill®** - Patented no-spill adapter for use with no-spill bottle caps



Power

Voltage	115, 220, 110
Frequency (Hz)	50/60
Power Consumption	5.42A / 602W / 110V
Cold Power Consumption	1.44A / 118W / 110V
Hot Power Consumption	4.33A / 500W / 110V
ES (kWh/24 hrs.)	0.86
% lower than ES Standard	1%

Hot Water System

Avg. Hot Water Temp at Nozzle @ 77°F Ambient (Cut-in / Cut-out Temp)	166.6°F 191.4°F
Hot Water ARI Rating	45, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	187°F / 203°F
Hot Water Flow Rate	0.67 - 0.73 oz./sec
Hot Tank Size (Liter : Gallon)	2.0L : 0.53G
Heat Band Wattage	450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	45.9°F / 42.2°F
Cold Water ARI Rating	5, 6 oz. < 50°F +/- 10%
Cold Thermostat Set Point	40°F +/- 10%
Cold Water Flow Rate	1.2 - 1.4 oz/sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	3.8 / 1.89 / 1.51 : 1 / 0.55 / 0.4

Weights and Measurements

Net Weight (Tatung Compressor / Huyai Compressor)	31.96 / 29.76
Gross Weight (Tatung Compressor / Huyai Compressor)	36.37 / 33.06
Max Distance from Drip Tray to Faucet (Inch : mm)	8 : 203.2
Faucet / Dispense Height (Inch : mm)	31.5 : 800
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	11.65x14.96x43.5 / 13x13.78x44.5
Container Load (20')	224
Container Load (40')	456
Container Load (40' HC)	456
Container Load (45' HC)	532
Certifications	UL Listed
Models (H&C)	GNB210p, GNB210p-CD

Warranty:

3 years: Sealed refrigeration system

2 years: Parts (electrical to include cold controls, relay overloads and PCB's)

phone: (909) 629-7301)**Canada:** (905) 302-7896**email:** info@aquabeve.com**web:** www.aquabeve.com